Magnetic Angle Fixtures and Hand Lifters

Processes

Stick, Plasma Cutting, MIG. Flux-Cored, TIG

Product Number

K3309-1 Multi Angle K3310-1 Pivot Angle

K3311-1 Manual Hand Lifter

K3312-1 Electric Hand Lifter

K3318-1 Mini Multi Angle

Work Angles

Multi Angle: 45°, 60°, 75°, 90°, 105°, 120°, 135°

Pivot Angle: Range from 22° to 270° Mini Multi Angle: 45°, 60°, 75°, 90°, 105°, 120°, 135°

Hand Lifters

Manual Hand Lifter:

Safe working load 60 lbs (27 kg)

Electric Hand Lifter:

Safe working load 60 lbs (27 kg)

Magnet Power

See back

Weight

See back

Dimensions See back

Metalworking Angle and **Lifting Devices with On/Off** Magnetic Fields.

Lincoln Electric magnetic fixturing tools can be used to position steel for tacking or lifting sheet steel at the work table. Make your workplace safe by minimizing hand contact with hot or sharp-edged steel.

FEATURES

- ▶ Three Angle Fixture Models Each intended for different material thicknesses or applications.
- ► Easy operation A 1/2 turn of the knob turns the magnet completely on or off for precise part positioning, part removal, or tool cleaning.
- ▶ Quick set-up Easy to use and sets up in seconds.
- **▶ Compact and lightweight** Great for tight spaces.
- ▶ Multi-angle surface Makes it easy to position on flat or round stock.

APPLICATIONS

- Welding
- Grinding



AÑOS DE GARANTIA PARTES Y MANO DE OBRA ANS DE GARANTIE



THE WELDING EXPERTS®



Multi Angle K3309-1

- Clever dual function- a workholding angle tool and a quick connect/ disconnect magnetic vise.
- Designed for small steel part fabrication including cutting, grinding, drilling and sanding.
- No batteries or electricity required.



Pivot Angle K3310-1

- Axis magnets mounted on pivot arms have one work surface on each side, enabling the tool to secure to a table or wall while simultaneously holding the work piece.
- Single lock on elbow for fast securing of the angle.
- Designed for repetitive work at uncommon angles.
- No batteries or electricity required.



Mini Multi Angle K3318-1

- Secures material at multiple angles.
- · Designed for small steel parts.
- Pipe notch for use on round stock.
- No batteries or electricity required.



Manual Hand Lifter K3311-1

- The handle has fixed or pivoting positions, alllowing use as a hand lifter or a sheet dragger.
- Designed for small steel part lifting and sheet dragging.
- Faster work with fewer injuries.
- No batteries or electricity required.



Electric Hand Lifter K3312-1

- Cordless electric hand lifter.
- Safety feature: battery power "on" light, blinking light if battery needs recharging.
- Designed for small steel part handling and removing parts from burn tables.
- Internal 4 volt rechargeable battery and charger included.
- Push button battery power operation for ease of use.
- Easily positioned on flat or round stock.

Product Name	Product Number	Work Angles	Magnetic Force lbs. (kg)	H x W x D inches (mm)	Net Weight Ibs. (kg)
Multi Angle Fixture	K3309-1	45°, 60°, 75°, 90°, 105°, 120°, 135°	400 (181)(2)	3.7 x 2.5 x 5.0 (95 x 65 x 129)	2.6 (1.2)
Pivot Angle Fixture	K3310-1	Range from 22° to 270°	200 (90)(1)	9.4 x 3.5 x 9.4 (240 x 91 x 240)	3.0 (1.4)
Mini Multi Angle Fixture	K3318-1	45°, 60°, 75°, 90°, 105°, 120°, 135°	80 (36)(2)	2.1 x 1.2 x 2.13 (55 x 32 x 59)	0.4 (0.2
Manual Hand Lifter	K3311-1	N/A	60 (27) hold on 3/16 in. thick steel or above	5.5 x 4.7 x 2.3 (140 x 120 x 60)	0.6 (0.27)
Electric Hand Lifter	K3312-1	N/A	60 (27)	8.2 x 6.7 x 2.9 (209 x 173 x 75)	2.0 (0.9)

⁽¹⁾ Hold capability on the bottom. Side hold will be less.

CUSTOMER ASSISTANCE POLICY

The business of The Lincoln Electric Company is manufacturing and selling high quality welding equipment, consumables, and cutting equipment. Our challenge is to meet the needs of our customers and to exceed their expectations. On occasion, purchasers may ask Lincoln Electric for information or advice about their use of our products. Our employees respond to inquiries to the best of their ability based on information provided to them by the customers and the knowledge they may have concerning the application. Our employees, however, are not in a position to verify the information provided or to evaluate the engineering requirements for the particular weldment. Accordingly, Lincoln Electric does not warrant or guarantee or assume any liability with respect to such information or advice. Moreover, the provision of such information or advice does not create, expand, or after any warranty on our products. Any express or implied warranty that might arise from the information or advice, including any implied warranty of merchantability or any warranty of fitness for any customers' particular purpose is specifically disclaimed.

Lincoln Electric is a responsive manufacturer, but the selection and use of specific products sold by Lincoln Electric is solely within the control of, and remains the sole responsibility of the customer. Many variables beyond the control of Lincoln Electric affect the results obtained in applying these types of fabrication methods and service requirements.

Subject to Change - This information is accurate to the best of our knowledge at the time of printing. Please refer to www.lincolnelectric.com for any updated information.



⁽²⁾ Hold varies depending on thickness of material and angle being used.